

ULTRA HIGH-PERFORMANCE ALS LABELING SYSTEMS

High performing, robust, industrial labeling systems for applying decorative, informative and branding labels in demanding environments for continuous operation.

MODULAR DESIGN – HIGH PERFORMANCE

The ALS 30x Labeling Series is our highest performance labeling system, equipped for the toughest labeling demands and environments. The innovative modular concept is specifically designed to ensure flexibility and optimize efficiency, even while applying labels of up to 229 mm (9").

ALS 306 HIGHLIGHTS

- High-performing labeling system for application of label materials up to 152 mm (6")
- Ideal system for high volume labeling with near-perfect application accuracy at speeds up to 60 mtr/min. (197' per min).

ALS 309 HIGHLIGHTS

- High-performing labeling system for application of label materials up to 229 mm (9")
- Ideal system for high volume labeling with near-perfect application accuracy at speeds up to 45 mtr/min. (148' per min).

COMMON TO BOTH

Flexibility:

- Modular components promote maximum efficiency and production uptime
- Quick and easy machine and line integration due to variable label roll positioning and mounting options

Productivity:

- The apply unit module and the power rewind module can easily be pulled out, allowing front access for easy maintenance and shorter downtimes

Intelligent:


- Internal warning in case new material supply is needed
- Automatic Product Speed Following (APSF) assures reliable and accurate label apply on conveyor belts with variable speeds

Connectivity:

- Offers all common connectivity features standard: ethernet, serial port, USB, SD card

MORE INFORMATION

To learn more about our Ultra High-performance labeling systems or to receive complete warranty information as well as other terms and conditions, please contact your NOVEXX Solutions representative, e-mail to printers@novexx.com or visit our website at www.novexx.com.



TECHNICAL INFORMATION

SPECIFICATIONS		ALS 306	ALS 309
Dispensing speed up to		60m/min	45m/min
Labels	Material	Self-adhesive label with liner, inside/outside winding possible	
	Label roll diameter unwinder	300 or 400 mm	
	Backing paper roll diameter rewinder	Up to 270 mm	
	Core diameter label roll	1.5"/3"/4"	
	Material width incl. backing paper	25-160 mm	25-233 mm
	Label length	20 – 600 mm (depending dispensing speed and required performance)	
Label stop accuracy	At dispensing edge	+/- 0.5 mm at fixed speed; +/- 1.0 mm at variable speed	
Electronics	Card slots	One SD card	
	Control panel	Graphic display 128 x 32 dots, 2 lines, 5 push buttons	
Data Interfaces	Serial	1x RS232, D-sub 9	
	Ethernet	1x 10/100 Base T/TX RJ 45	
	USB	1x device, 1x host	
	Remote display	1x RS485 (mini-DIN 6)	
	Internal Interfaces	Applicator interface (optional)	
PLC Interfaces	Opto-isolated	D-sub 15 connector , optional on 8-pin M12	
	Output	4x PNP, 24V, max. 500 mA	
	Total max.	1500 mA	
	Input	3x PNP/NPN, 24V	
External sensor interfaces	Opto-isolated	4-pin M12 connector	
	Label sensor	Optical Label sensor	
	Alternative label sensors	PNP/NPN, 24V	
	Product sensor/APSF sensor/ external OD sensor	PNP/NPN, 24V	
Status messages	Dispensing stops when	1. Label stock ends 2. Missing label counter is exceeded 3. No label gap found	
Test functions		Automatic diagnosis after powering on	
IP-protection	Class	Standard 21, optional 54	
Dimensions/ Environment	H*W*D (mm), base module	389*726*386	389*726*470
	With unwinder Top	802*726*386	802*726*470
	Weight (incl. one unwinder)	54 kg	56 kg
	Mains voltages/power consumption	100/240 V (AC); max. 5.1/2.1 A	
	Operating temperature	5 – 40° C	
	Humidity	30 – 85%, not condensing	
	Qualifications	CE, TUV/CS, FCC, CCC, GOST, NRTL (US/CA)	
Label positions		Top/bottom/side; direct apply or by use of applicator	
Options	L-shape dispensing edges, L-shape rotating fixtures standard or adjustable (EURO-fixtures), internal label roll OD kit, tandem function, applicator interface, various applicators, IP54 kit, rotary encoder for APSF (automatic product speed follower), remote display, labelweb splice unit, capacitive label sensor.		

Novexx Solutions GmbH DEUTSCHLAND

Ohmstrasse 3
D-85386 Eching
Tel. +49 (0)8165 925 299
info.deutschland@novexx.com

Novexx Solutions S.A.S. FRANCE

Tel. +33 (0)825 82 61 52
info.france@novexx.com

Novexx Solutions B.V. NEDERLAND

Tel. +31 (0)302 63 22 33
info.nederland@novexx.com

Novexx Solutions B.V. BELGIE

Tel. +32 (0)2 377 8002
info.belgie@novexx.com

Novexx Etiketleme Sistemleri Tic. A.Ş. TÜRKIYE

Tel. +90 216 564 81 81
info.turkiye@novexx.com

Novexx Solutions GmbH ITALIA

Tel. +39 0331 1855511
info.italia@novexx.com

Novexx Solutions GmbH FILIAL SVERIGE

Tel. +46 (0)31 68 30 40
info.sverige@novexx.com

manroland India Pvt. Ltd. INDIA

Tel. +91 (11) 47002900
info.india@novexx.com

Novexx Solutions USA

Tel. +1 610 4730751
info.usa@novexx.com

Novexx Solutions ASIA

Tel. +86 (021) 2215 7665
info.asia@novexx.com

Novexx Solutions GmbH POLSKA

Tel. +48 (0)605957108
info.polska@novexx.com

The information contained herein is believed to be reliable but NOVEXX Solutions makes no representations concerning the accuracy or correctness of the data. The information, like any other should be confirmed independently for the particular end user conditions to ensure the proposed labeling meets the relevant requirements and regulations. NOVEXX Solutions shall have no liability whatsoever, regardless of any legal theory, arising out of your use or reliance on the information contained herein and in no event shall NOVEXX Solutions be held liable for consequential, indirect or incidental damages. NOVEXX Solutions liability is limited to the replacement value of defective product. Products, information and specifications are subject to change without notice.

© 2015 Novexx Solutions GmbH, All Rights Reserved. Third party trademarks and/or trade names may be used herein are the property of their respective owner(s).