

MULTI-FUNCTIONAL ALS LABELING SYSTEMS

Industrial labeling systems for applying labels to products that increase brand awareness and enhance shelf appearance.

MULTI-FUNCTIONAL INDUSTRIAL LABELING SYSTEMS

ALS Labeling Systems can be configured to fit virtually any industrial labeling challenge. Whether it's applying at high or low application speed, using small or wide labels or working in wet or dry environments, we have the right solution in our reliable, durable ALS 104, 204, 206, 256 and 209 series label systems.

RECOMMENDED LABELING APPLICATIONS

- Product
- Decorative
- Canned Goods
- Hygiene
- Household Goods
- Electronics
- Shipping
- Cosmetics
- Food and Beverage
- Chemicals
- Building Materials

FAST AND FLEXIBLE

- Combine extreme robustness with high-performance
- Configured for demanding performance in continuous operation, 24 hours a day, 7 days a week
- Modular concept for easy integration into a unit in your existing system in exchange for another
- Features bottom, side and top labeling with three different fixing options
- Dispensing edge can be rotated by up to 90° for even greater flexibility

OPTION KIT MAKES ALS FAMILY PERFECT FOR MULTIPLE ENVIRONMENTS

IP 65 kits provide protection for the applicators and facilitate easy cleaning, which is particularly important in the food industry. With the addition of the IP65 kit, the ALS family can also be used in humid or dusty environments.

MORE INFORMATION

To learn more about our Multi-functional ALS labeling systems or to receive complete warranty information as well as other terms and conditions, please contact your NOVEXX Solutions representative, e-mail to printers@novexx.com or visit our website at www.novexx.com.



MULTI-FUNCTIONAL ALS LABELING SYSTEMS

SPECIFICATIONS - ALS 104 RH/LH

| | | |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| Dispensing speed up to | Up to 30 m/min | |
| Labels | Material | Self-adhesive label with liner; inside/outside winding possible |
| | Label roll diameter unwinder | up to 300mm |
| | Backing paper roll diameter rewinder | up to 200mm |
| | Core diameter | 1.5"/3"/4" |
| | Material width incl. backing paper | 10 – 110mm |
| | Label length | 5 - 600mm |
| Label stop accuracy | At dispensing edge | +/- 0.5mm at fixed speed; +/- 1.0mm at variable speed |
| Electronics | Card slots | none |
| | Control panel | Graphical display, 128 x 32 dots, two lines, five push buttons |
| Data Interfaces | Serial | 1x RS232 |
| | Ethernet | none |
| | USB | none |
| | Remote display | 1x RS422 (Mini-DIN 6) |
| PLC Interfaces | Opto-isolated | Sub-D15 |
| | Output | 3X PNP, 24V |
| | Input | none |
| | Parallel function to PNP-output | optional on 8 pin M12 connector: PNP/NPN, 24V |
| External sensor interfaces | Opto-isolated | 4-pin M12 connectors |
| | Label sensor | OPT242-P800 sensor |
| | Alternative sensor | PNP/NPN, 24V |
| | Product sensor/APSF sensor/OD sensor | PNP/NPN, 24V |
| Status messages | Status messages/Test functions: | No gap found/missing labels count |
| Test functions | | Automatic diagnosis after powering on |
| IP-protection | Class | Standard 21, optional IP65 |
| Noise | Max. | < 70 dB [A] |
| Dimensions/Environment | H x W x D [mm] | 492 x 488 x 371 |
| | Weight | 33 kg |
| | Mains voltage | 115V (AC) at 60 Hz power frequency; 230 V (AC) at 50 Hz power frequency |
| | Operating temperature | 5-40°C |
| | Humidity | 30 to 85% non-condensing |
| | Qualifications | CE, TUV/GS, FCC, CCC, GOST, NRTL [US/CA] |
| Label positions | | top/side/bottom; direct apply |
| Options | L-shape dispensing edge, V-shape dispensing edge, external OD sensor, external remote control display, IP 65 kit, rotary encoder for APSF (automatic product speed follower) | |

MULTI-FUNCTIONAL ALS LABELING SYSTEMS

| SPECIFICATIONS | | ALS 204 RH/LH | ALS 206 RH/LH | ALS 209 RH/LH | ALS 256 RH/LH |
|-----------------------------|-----------------------------------------------|--------------------------------------------------------------------------------------|---------------|---------------|---------------|
| Dispensing speed up to | | 40m/min | 30m/min | 25m/min | 50m/min |
| Labels | Material | self-adhesive label with liner; inside/outside winding possible | | | |
| | Label roll diameter unwinder | up to 300mm | | | |
| | Backing paper roll diameter rewinder | up to 200mm | | | |
| | Core diameter | 1.5"/3"/4" | | | |
| | Material width incl. backing paper | 10-110mm | 10-160mm | 50-233mm | 10-160mm |
| | Label length | 5-600mm | | 50-600mm | 5-600mm |
| Label stop accuracy | At dispensing edge | +/-0.5 mm at fixed speed; +/-1.0 mm at variable speed | | | |
| Electronics | Card slots | Slot for one SD-card | | | |
| | Control panel | Graphical display 128 x 32 dots, 2 lines, 5 push buttons | | | |
| Data Interfaces | Serial | 1x RS232C, D-Sub 9, max. 115200 Baud | | | |
| | Ethernet | 1x 10/100 Base T/TX RJ45 | | | |
| | USB | 1x device, 1x host | | | |
| | Remote display | 1x RS485 (mini-DIN 6) | | | |
| | Internal interfaces | Applicator interface (optional) | | | |
| PLC Interfaces | Opto-isolated | Sub D15 or optional two 8-pin M12 | | | |
| | Output | 4x PNP, 24 V, max. 500mA/Output | | | |
| | Input | 3x PNP/NPN, 24 V | | | |
| External sensor interfaces: | Opto-isolated | 4-pin M12 connector | | | |
| | Label sensor | Optical Label sensor | | | |
| | Alternative sensors | PNP/NPN, 24 V | | | |
| | Product sensors/ APSF sensor/ OD sensor | PNP/NPN, 24 V | | | |
| Status messages | Dispensing stops, when | 1. Label stock ends or 2. Missing label counter is exceeded or 3. No gap found | | | |
| Test functions: | | Automatic diagnosis after powering on | | | |
| IP-protection | Class | Standard 21, option 65 | | | Standard 21 |
| Noise: | Max. | < 70 dB [A] | | | |

MULTI-FUNCTIONAL ALS LABELING SYSTEMS

| SPECIFICATIONS | | ALS 204 RH/LH | ALS 206 RH/LH | ALS 209 RH/LH | ALS 256 RH/LH |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|-----------------|-----------------|--------------------------------------------------|
| Dimension/ Environment | H x W x D [mm] | 492 x 488 x 371 | 492 x 488 x 402 | 492 x 488 x 505 | 492 x 488 x 402 |
| | Weight | 36 kg | 36 kg | 38 kg | 40 kg |
| | Mains voltage/ power consumption | 115V (AC) at 60 Hz power frequency; 230 V (AC) at 50 Hz power frequency | | | 100-240 V (AC) at 60/50 Hz power frequency |
| | Operating temperature | 5-40°C | | | |
| | Humidity | 30-85%, not condensing | | | |
| | Qualification | CE, TUV/GS, FCC, CCC, GOST, NRTL [US/CA] | | | |
| Labeling positions | Input | Top/side/bottom. Direct apply or by use of applicator | | | |
| Options | L-shape dispensing edge, V-shape [ALS 204 only] dispensing edge, external OD sensor, different sensors and applicators, external remote control display, Tandem function, Applicator Interface, IP 65 kit (for ALS 204, ALS 206 and ALS 209), adjustable fixture for L-shape, rotary encoder for APSF (automatic product speed follower) | | | | |

Novexx Solutions GmbH DEUTSCHLAND

Ohmstrasse 3
D-85386 Eching
Tel. +49 (0)8165 925 299
info.deutschland@novexx.com

Novexx Solutions S.A.S. FRANCE

Tel. +33 (0)825 82 61 52
info.france@novexx.com

Novexx Solutions B.V. NEDERLAND

Tel. +31 (0)302 63 22 33
info.nederland@novexx.com

Novexx Solutions B.V. BELGIE

Tel. +32 (0)2 377 8002
info.belgie@novexx.com

Novexx Etiketleme Sistemleri Tic. A.Ş. TÜRKIYE

Tel. +90 216 564 81 81
info.turkiye@novexx.com

Novexx Solutions GmbH ITALIA

Tel. +39 0331 1855511
info.italia@novexx.com

Novexx Solutions GmbH FILIAL SVERIGE

Tel. +46 (0)31 68 30 40
info.sverige@novexx.com

manroland India Pvt. Ltd. INDIA

Tel. +91 (11) 47002900
info.india@novexx.com

Novexx Solutions USA

Tel. +1 610 4730751
info.usa@novexx.com

Novexx Solutions ASIA

Tel. +86 (021) 2215 7665
info.asia@novexx.com

Novexx Solutions GmbH POLSKA

Tel. +48 (0)605957108
info.polska@novexx.com

The information contained herein is believed to be reliable but NOVEXX Solutions makes no representations concerning the accuracy or correctness of the data. The information, like any other should be confirmed independently for the particular end user conditions to ensure the proposed labeling meets the relevant requirements and regulations. NOVEXX Solutions shall have no liability whatsoever, regardless of any legal theory, arising out of your use or reliance on the information contained herein and in no event shall NOVEXX Solutions be held liable for consequential, indirect or incidental damages. NOVEXX Solutions liability is limited to the replacement value of defective product. Products, information and specifications are subject to change without notice.

© 2015 Novexx Solutions GmbH, All Rights Reserved. Third party trademarks and/or trade names may be used herein are the property of their respective owner(s).